

Flats – cold drawn

According to EN 10277-1, tolerances h11,
grade acc. to EN 10088-3: 1.4301 / 1.4307

Méplats – étirés à froid

Conformes à EN 10277-1, tolérances h11,
nuance selon EN 10088-3: 1.4301 / 1.4307

Flachstahl – kalt gezogen

Gemäß EN 10277-1, Toleranzen h11,
Güte nach EN 10088-3: 1.4301 / 1.4307



a	t																
	2	3	4	5	6	8	10	12	15	20	25	30	35	40	45	50	60
8	0.13	0.19	0.26	0.32	0.38												
10	0.16	0.24	0.32	0.40	0.48	0.64											
12		0.29	0.38	0.48	0.57	0.76	0.96										
15		0.36	0.48	0.60	0.72	0.96	1.20	1.44									
16		0.38	0.51	0.64	0.77	1.02	1.28	1.54									
18		0.43	0.58	0.72	0.86	1.15	1.44	1.73	2.16								
20		0.48	0.64	0.80	0.96	1.44	1.60	1.92	2.40								
25		0.60	0.80	1.00	1.20	1.60	2.00	2.40	3.00	4.00							
30		0.72	0.96	1.20	1.44	1.92	2.40	2.88	3.60	4.80	6.00						
35		0.84	1.12	1.40	1.68	2.24	2.80	3.36	4.20	5.60	7.00	8.40					
40		0.96	1.28	1.60	1.92	2.56	3.20	3.84	4.80	6.40	8.00	9.60	11.2				
45		1.08	1.44	1.80	2.16	2.72	3.60	4.32	5.40	7.20	9.00	10.8	12.6	14.4			
50		1.20	1.60	2.00	2.40	3.20	4.00	4.80	6.00	8.00	10.0	12.0	14.0	16.0			
60		1.44	1.92	2.40	2.88	3.84	4.80	5.76	7.20	9.60	12.0	14.4	16.8	19.2	21.6	24.0	
70			2.24	2.80	3.36	4.48	5.60	6.56	8.40	11.2	14.0	16.8	19.6	24.0	25.2	28.0	36.0
80			2.56	3.20	3.84	5.12	6.40	7.68	9.60	12.8	16.0	19.2	22.4	25.6	28.8	32.0	38.4
90				3.60	4.32	5.76	7.20	8.64	10.8	14.4	18.0	21.6	25.2	28.8	32.4	36.0	43.2
100				4.00	4.80	6.40	8.00	9.60	12.0	16.0	20.0	24.0	28.0	32.0	36.0	40.0	48.0
Poid – Weight – Gewicht kg/m																	



Flats – cold drawn

According to EN 10277-1, tolerances h11,
grade acc. to EN 10088-3: 1.4301 / 1.4307

Méplats – étirés à froid

Conformes à EN 10277-1, tolérances h11,
nuance selon EN 10088-3: 1.4301 / 1.4307

Flachstahl – kalt gezogen

Gemäß EN 10277-1, Toleranzen h11,
Güte nach EN 10088-3: 1.4301 / 1.4307



a	t																
	2	3	4	5	6	8	10	12	15	20	25	30	35	40	45	50	60
120					5.76	7.68	9.60	11.5	14.4	19.2	24.0	28.8	33.6	38.4	43.2	48.0	57.6
125					6.00	8.00	10.0	12.0	15.0	20.0	25.0	30.0	35.0	40.0	45.0	50.0	60.0
130					6.24	8.32	10.4	12.5	15.6	20.8	26.0	31.2					
140					6.72	8.96	11.2	13.4	16.8	22.4	28.0	33.6					
150					7.20	9.60	12.0	14.4	18.0	24.0	30.0	36.0					
160					7.68	10.2	12.8	15.4	19.2	25.6	32.0	38.4					
180					8.64	11.5	14.4	17.2	21.6	28.8	36.0	43.2					
200					9.60	12.8	16.0	19.2	24.0	32.0	40.0	48.0					
220						14.1	17.6	21.1	26.4	35.2							
250						16.0	20.0	24.0	30.0	40.0							
Poid – Weight – Gewicht kg/m																	