



KEY STEEL



COLD DRAWN PROFILES


KEY STEEL COLD DRAWN



STAINLESS STEEL

Product Description

According to DIN 6880,
Tolerances h9
Grade according to EN 10088-3
Surface condition: bright



General properties

Designation		Dimensions		
	G kg/m	a mm	t mm	A mm ² ×10 ²
3 × 3	0.072	3	3	0.09
4 × 4	0.128	4	4	0.16
5 × 3	0.12	5	3	0.15
5 × 5	0.2	5	5	0.25
6 × 6	0.288	6	6	0.36
8 × 5	0.32	8	5	0.4
8 × 6	0.384	8	6	0.48
8 × 7	0.448	8	7	0.56
10 × 6	0.48	10	6	0.6
10 × 8	0.64	10	8	0.8
12 × 6	0.576	12	6	0.72
12 × 8	0.768	12	8	0.96
12 × 10	0.96	12	10	1.2
14 × 6	0.672	14	6	0.84
14 × 9	1.008	14	9	1.26
16 × 10	1.28	16	10	1.6
18 × 7	1.008	18	7	1.26
18 × 11	1.584	18	11	1.98
20 × 8	1.28	20	8	1.6
20 × 12	1.92	20	12	2.4
22 × 9	1.58	22	9	1.98
22 × 14	2.46	22	14	3.08
25 × 14	2.8	25	14	3.50
28 × 10	2.24	28	10	2.8
28 × 16	3.58	28	16	4.48
32 × 18	4.61	32	18	5.76
36 × 20	5.76	36	20	7.2
40 × 22	7.04	40	22	8.8
45 × 25	9.00	45	25	11.25

Other custom sizes are available upon request